



# Town & Country

## SPECIFICATIONS

## 2014 Chrysler Town & Country

### SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.

All dimensions are in inches (millimeters) unless otherwise noted.

All dimensions measured at curb weight with standard tires and wheels.

#### GENERAL INFORMATION

Vehicle Type	Multipurpose vehicle
Assembly Plant	Windsor, Ontario, Canada
EPA Vehicle Class	Multipurpose vehicle
Introduction Date	December 2008

#### BODY/CHASSIS

Layout	Transverse front engine, front-wheel drive
Construction	Unitized steel with hinged front doors; sliding left and right side doors—power available; rear liftgate with gas props—power available

#### ENGINE: 3.6-LITER, GASOLINE, DOHC, 24-VALVE, V-6

Availability	Standard
Type and Description	60-degree bank angle, liquid-cooled, with three-plenum intake manifold, electronically-controlled manifold tuning valve and short-runner valves
Displacement	3,605 cu. cm
Bore x Stroke	96 x 83
Valve System	DOHC, 24 valves, hydraulic, roller finger followers
Fuel Injection	Sequential, multi-port, electronic
Construction	High-pressure die-cast A380 aluminum block with iron liners and semi-permanent mold A319 aluminum heads
Compression Ratio	10.2:1
Power (SAE net)	283 bhp (211 kW) @ 6,400 rpm
Torque (SAE net)	260 lb.-ft. (353 N•m) @ 4,400 rpm
Max. Engine Speed	6,800 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2—acceptable
Oil Capacity	6 qts. with dry filter
Coolant Capacity	10.3 qts. (9.75-liter)
Emission Controls	Dual catalytic converter, four heated oxygen sensors, electronic EGR, and internal engine features <sup>(d)</sup>



# Town & Country

## SPECIFICATIONS

EPA Fuel Economy mpg (city/hwy), NAFTA Markets 17/25

Assembly Plant Trenton Engine Plant, Trenton, Mich.

(d) Meets Federal Tier 2, Bin 5 emission requirements and ULEV II requirements in California, Massachusetts, New York, Maine, Vermont, Connecticut, Pennsylvania, Rhode Island, New Jersey, Oregon and Washington. Meets Euro IV emissions requirements.

### TRANSMISSION: 62TE, AUTOMATIC, SIX-SPEED OVERDRIVE

Availability Standard

Description 6-speed, adaptive electronic control, electronically-modulated torque converter clutch

#### Gear Ratios

1st 3.90

2nd 2.69

3rd 2.16

4th Upshift – 1.37 WOT kickdown – 1.49

5th 0.95

6th 0.65

Reverse 3.04

Transfer Ratio 0.95

Final Drive Ratio 3.16

Overall Top Gear 2.068

### ELECTRICAL SYSTEM

Alternator 160A

Battery 730 CCA, maintenance-free

### SUSPENSION

Front Independent MacPherson strut, coil over gas-charged shock absorbers, stabilizer bar with isolated suspension cradle

Rear Twist-beam axle with coil springs, track bar, gas-charged shock absorbers; self-leveling shock absorbers optional



# Town & Country

## SPECIFICATIONS

### STEERING

Type	Power rack and pinion
Overall Ratio	14.3:1
Turning Diameter (curb-to-curb)	39.1 ft. (11.92 m)
Steering Turns (lock-to-lock)	2.90
P/S pump	Hydraulic

### BRAKES

Type	All — Power assist, 9 x 9 (230 x 230) tandem-diaphragm vacuum, ABS
Availability	U.S. — Standard on all models
Front	
Rotor size and type	13.0 x 1.1 (330mm x 28mm) vented rotor
Caliper size and type	51 mm twin-piston caliper
Swept area	73.6 sq. in. (475 sq. cm)
Rear	
Rotor size and type	12.9 x 0.47 (328mm x 12mm) solid rotor
Caliper size and type	45 mm single-piston IPB caliper
Swept area	66.5 sq. in. (429 sq. cm)

### DIMENSIONS AND CAPACITIES

Wheelbase	121.2 (3,078.2)
Overhang—Front	37.8 (960.9)
Overhang—Rear	43.8 (1,112.1)
Track—Front	65.6 (1,665.5)
Track—Rear	64.8 (1,647.0)
Overall Length	202.8 (5,151.2)
Overall Width	78.7 (1,998.2)
Overall Width with Mirrors	88.5 (2,246.8)
Overall Height	66.9 (1,751.0)
Liftover Height	24.0 (609.0)
Cargo Width at Wheelhouse	48.8 (1,239.0)
Maximum Cargo Height	46.16 (1,172.4)
Approach Angle (degrees)	14.7
Ramp Breakover Angle (degrees)	14.6
Departure Angle (degrees)	19.2



Minimum Running Ground Clearance (curb load)	5.8 (148)
Frontal Area	32.3
Drag Coefficient (Cd)	.316
Aero CdA	10.2
Fuel Tank Capacity, (gallons / (L))	20 (76)
Gross Vehicle Weight Rating (GVWR), (lbs. / kg)	6,050 (2,744.2)
Towing Capacity, (lbs. / kg)	3,600 (1,632.9) — with Trailer-tow Prep Package
U.S. Curb Weight, (lbs. / kg)	4,652 (2,115) — Automatic transaxle
Weight Distribution (percent front/rear)	56/44

**ACCOMMODATIONS**

Seating Capacity (front/second/third rows)	2/2/3
Total Interior Passenger Volume, (cu. ft. / cu. m)	163.5 (4.63) / 156.1 (4.42)
Front	
Head Room	39.8 (1,011.9)
Head Room with Sunroof	37.2 (946.0)
Leg Room	40.7 (1,034.4)
Shoulder Room	63.7 (1,618.6)
Hip Room	58.4 (1,484.5)
Seat Travel	8.7 (220)
Recliner Angle Range (degrees)	Manual recline: 88 Power recline: 59
Front Passenger Volume, cu. ft.	58.4
Intermediate	
Head Room	39.3 (998.9)
Legroom	36.5 (925.9)
Knee Clearance	3.2 (81.4)
Shoulder Room	64.1 (1,628.1)
Hip Room	65.0 (1,650.8)
Intermediate Passenger Volume, cu. ft. (cu. m)	54.0 (1.53)



<b>Rear</b>	
Head Room	37.9 (962.9)
Legroom	32.7 (829.7)
Knee Clearance	6.0 (153.0)
Shoulder Room	62.0 (1,574.6)
Hip Room	48.7 (1,237.7)
Rear Passenger Volume, cu. ft. (cu. m)	51.1 (1.45)
<b>Cargo Volume</b>	
Maximum Cargo Volume, (cu. ft. / cu. m)	143.8 (4.1)
Behind Second-row Seats, (cu. ft. / cu. m)	83.3 (2.34)
Aft of Third-row Seat, (cu. ft. / cu. m)	33.0 (0.93)
Total Passenger plus Cargo Volume, (cu. ft. / cu. m)	195.8 (5.54)

**WHEELS**

Availability	Standard on Town & Country Touring and Touring-L
Type and Material	Cast aluminum fully-painted Satin Silver
Size	17 x 6.5
Availability	Standard on Town & Country S
Type and Material	Cast aluminum polished with Gloss Black painted pockets
Size	17 x 6.5
Availability	Standard on Town & Country 30 <sup>th</sup> Anniversary
Type and Material	Cast aluminum polished with Satin Carbon painted pockets
Size	17 x 6.5
Availability	Standard on Town & Country Limited and optional on Touring L
Type and Material	Cast aluminum Physical Vapor Deposition (PVD) finish on Limited, Bright finish on Touring L
Size	17 x 6.5



# Town & Country

## SPECIFICATIONS

### TIRES

Availability	Standard on Town & Country Touring-L, 30 <sup>th</sup> Anniversary and Limited
Size and Type	P225/65R17 BSW, All-season Touring
Model	Michelin Energy Saver A/S
Availability	Standard on Town & Country Touring, S
Size and Type	P225/65R17 BSW, All-season Touring
Model	Kumho Solus KH16
Parking Brake Type	Integral parking brake
Four-wheel Anti-lock Brake System (ABS)	Standard
Electronic Stability Control (ESC)	Standard
All-speed Traction Control	Standard
Brake Assist	Standard

