



2016 RAM 1500 SPECIFICATIONS

2016 Ram 1500 SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.
All dimensions are in inches (millimeters) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.*

GENERAL INFORMATION

Vehicle Type	Regular Cab, Quad Cab, and Crew Cab, 2WD, 4WD
Assembly Plant	Regular Cab: Saltillo Truck Assembly, Saltillo, Mexico Quad Cab: Warren Truck Assembly Plant, Warren, Michigan Crew Cab: Warren Truck Assembly Plant, Warren, Michigan and Saltillo Truck Assembly, Saltillo, Mexico
EPA Vehicle Class	Standard Pickup

BODY/CHASSIS

Layout	2WD — Longitudinal, front engine 4WD — Longitudinal, front engine, transfer case
Construction	2WD — Ladder-type frame, steel cab, double-wall steel pickup box 4WD — Ladder-type frame, steel cab, double-wall steel pickup box

ENGINE: 3.6-LITER PENTASTAR V-6

Type and Description	60-degree V-type, liquid-cooled
Displacement	220 cu. in. (3,604 cu. cm)
Bore x Stroke	3.78 x 3.27 (96.0 x 83.0)
Valve System	Chain-driven DOHC, 24 valves and hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Aluminum deep-skirt block, aluminum alloy heads
Compression Ratio	10.2:1
Power	305 hp (224 kW) at 6,400 rpm
Torque	269 lb.-ft. (364 N•m) at 4,175 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2, E85-compatible
Oil Capacity	6.0 quarts (5.7 liters)
Coolant Capacity	14.0 quarts (13.25 liters)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors
EPA Fuel Economy mpg (city/hwy)	18/25



2016 RAM 1500 SPECIFICATIONS

ENGINE: 3.0-LITER ECODIESEL V-6

Type and Description	60-degree V-type, liquid-cooled
Displacement	182 cu. in. (2988 cu. cm)
Bore x Stroke	3.27 x 3.60 (83 x 92)
Valve System	Chain-driven DOHC, 24 valves
Fuel Injection	Common-rail, 2000 bar, Solenoid Injectors
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	16.5:1
Power	240 hp (179 kW) at 3,600 rpm
Torque	420 lb.-ft. (569 N•m) at 2,000 rpm
Max. Engine Speed	4,800 rpm (electronically limited)
Fuel Requirement	Ultra Low-sulfur diesel
Oil Capacity	10.5 quarts (10 liters)
Coolant Capacity	12 quarts (11.4 liters)
Emission Controls	Cooled EGR, oxidation catalyst, diesel particulate filter, SCR w/urea injection
EPA Fuel Economy mpg (city/hwy)	21/29

ENGINE: 5.7-LITER HEMI® V-8

Type and Description	90-degree V-8, liquid-cooled
Displacement	345 cu. in. (5,654 cu. cm)
Bore x Stroke	3.92 x 3.58 (99.5 x 90.9)
Valve System	Variable-cam timing, pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.5:1
Power	395 hp (291 kW) @ 5,600 rpm
Torque	410 lb.-ft. (556 N•m) @ 3,950 rpm
Max. Engine Speed	5,800 rpm
Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2 — recommended Unleaded regular, 87 octane (R+M)/2 — acceptable
Oil Capacity	7.0 quarts (6.6 liters)
Coolant Capacity	14.0 quarts (13.33 liters)
Emission Controls	Three-way catalytic converters, heated oxygen sensors □ and internal engine features



RAM

2016 RAM 1500 SPECIFICATIONS

EPA Fuel Economy mpg (city/hwy) eight-speed automatic	15/22
---	-------

EPA Fuel Economy mpg (city/hwy) six-speed automatic	14/20
---	-------

TRANSMISSION: 65RFE AUTOMATIC SIX-SPEED

Availability	Available with 5.7-liter HEMI V-8 equipped trucks
--------------	---

Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronic converter clutch
-------------	---

Gear Ratios

1st	3.00
-----	------

2nd	1.67
-----	------

3rd	1.50
-----	------

4th	1.00
-----	------

5th	0.75
-----	------

6th	0.67
-----	------

Reverse	3.00
---------	------

Axle Gear Ratios	3.21, 3.55, 3.92
------------------	------------------

TRANSMISSION: TORQUEFLITE 845RE EIGHT-SPEED AUTOMATIC

Availability	Standard with 3.6-liter Pentastar V-6
--------------	---------------------------------------

Description	Adaptive electronic control, automatic or Electronic Range Select (ERS) manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
-------------	---

Gear Ratios

1st	4.71
-----	------

2nd	3.14
-----	------

3rd	2.10
-----	------

4th	1.67
-----	------

5th	1.29
-----	------

6th	1.00
-----	------

7th	0.84
-----	------

8th	0.67
-----	------

Reverse	3.30
---------	------

Axle Gear Ratios	3.21, 3.55, 3.92 (Rebel only)
------------------	-------------------------------



2016 RAM 1500 SPECIFICATIONS

TRANSMISSION: ZF TORQUEFLITE 8HP70 EIGHT-SPEED AUTOMATIC

Availability	Standard with 3.0-liter EcoDiesel V-6 and select 5.7-liter HEMI V-8 equipped trucks
Description	Adaptive electronic control, automatic or ERS manual control. Five clutch-pack design with only two open clutches in any gear. Torque converter lock with turbine torsional damper for low lock-up speeds in 1st through 8th gear
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30
Axle Gear Ratios	3.21 (excluding 3.0-liter EcoDiesel V-6), 3.55 (excluding 5.7-liter HEMI V-8), 3.92

TRANSFER CASE: BW 44-45 PART-TII

Availability	3.6-liter Pentastar V-6 4x4, and 5.7-liter HEMI V-8 4x4
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	2WD High; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Center Differential Type	None

TRANSFER CASE: BW 44-44 ON-DEM

Availability	3.0-liter EcoDiesel V-6 4x4, and 5.7-liter HEMI V-8 4x4
Shift Mechanism	Electric
Available Speeds	Two-speed
Operating Modes	2WD High; 4WD Auto; 4WD High, Locked; Neutral; 4WD Low, Locked
Low-range Ratio	2.64
Center Differential Type	None



2016 RAM 1500 SPECIFICATIONS

AXLES

Front	ZF 215 mm
Rear	C235 mm (available limited slip)
Available Ratios	3.21, 3.55, 3.92

ELECTRICAL SYSTEM

Architecture	Powernet
Alternator	160-amp, 180-amp, 220-amp (Stop-start system and Special Services Package) 230-amp (3.0-liter EcoDiesel V-6)
Battery	Group 65, low-maintenance 730 CCA (Stop-start features 800 CCA absorbed glass mat)

SUSPENSION

Front	Upper and lower "A" arms, coil springs, twin-tube shock absorbers, stabilizer bar. Optional air suspension replaces twin-tube shock absorbers and coil springs. Rebel features Bilstein monotube shocks with air suspension
Rear	Five-link with track bar, coil springs, stabilizer bar, twin-tube shock absorbers, solid axle. Optional air suspension replaces twin-tube shock absorbers and coil springs. Rebel features Bilstein monotube shocks with air suspension

BRAKES

Front	
Size and Type	13.2 x 1.1 (336 x 28) vented disc with 2.13 (54) two-piston pin-slider caliper and anti-lock braking system (ABS)
Swept Area	292 sq. in. (1,884 sq. cm)
Rear	
Size and Type	13.8 x 0.87 (352 x 22) disc with 2.13 (54) single-piston pin-slider caliper and ABS
Swept Area	274 sq. in. (1,768 sq. cm)
Power-assist	Dual-rate, tandem diaphragm vacuum

AIR BAGS

Regular Cab	6
Quad Cab	6
Crew Cab	6

**RAM**

2016 RAM 1500 SPECIFICATIONS

STEERING

Power-assist

Regular Cab	2WD	2WD	4WD	4WD
Box Length	6-ft. 4-in.	8-ft.	6-ft. 4-in.	8-ft.
Wheelbase (nominal)	120.5 (3,061)	140.5 (3,569.2)	120.5 (3,061)	140.5 (3,569.2)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire -ft. (m)	39.5 (12.0)	45.1 (13.7)	39.8 (12.1)	45.4 (13.8)
Turning Diameter – 20-in. Tire -ft. (m)	39.3 (12.0)	44.9 (13.7)	39.8 (12.1)	45.5 (13.9)
Turning Diameter – 17-in. Outdoorsman [®] Tire – ft. (m)	N/A	N/A	39.4 (12.0)	45.0 (13.7)

Quad Cab	2WD	4WD
Box Length	6-ft. 4-in.	6-ft. 4-in.
Wheelbase (nominal)	140.5 (3,569.2)	140.5 (3,569.2)
Overall Steering Ratio	17.9:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.3	3.3
Turning Diameter – 17-in. Tire -ft. (m)	45.1 (13.7)	45.4 (13.8)
Turning Diameter – 20-in. Tire -ft. (m)	44.9 (13.7)	45.5 (13.9)
Turning Diameter – 17-in. Outdoorsman Tire – ft. (m)	44.8 (13.7)	45.0 (13.7)

Crew Cab	2WD	2WD	4WD	4WD
Box Length	5-ft. 7-in.	6-ft. 4-in.	5-ft. 7-in.	6-ft. 4-in.
Wheelbase (nominal)	140.5 (3,061)	149.5 (3,569.2)	140.5 (3,569.2)	149.5 (3,569.2)
Overall Steering Ratio	19.1:1	17.9:1	19.1:1	17.9:1
Steering Wheel Turns (lock-to-lock)	3.5	3.3	3.5	3.3
Turning Diameter – 17-in. Tire -ft. (m)	39.5 (12.0)	45.1 (13.7)	39.8 (12.1)	45.4 (13.8)
Turning Diameter – 20-in. Tire -ft. (m)	39.3 (12.0)	44.9 (13.7)	39.8 (12.1)	45.5 (13.9)
Turning Diameter – 17-in. Outdoorsman Tire – ft. (m)	N/A	N/A	39.4 (12.0)	45.0 (13.7)

**RAM****2016 RAM 1500
SPECIFICATIONS****DIMENSIONS AND CAPACITIES****Cargo Box**

Nominal Box Size	5-ft. 7-in. (Crew)	6-ft. 4-in. (Regular, Quad, or Crew)	8-ft. (Regular)
SAE volume, cu. ft. (cu m)	50.3 (1.4)	57.5 (1.6)	74.7 (2.1)
Length at Floor, Tailgate Closed	67.4 (1,712.4)	76.3 (1,938.5)	98.3 (2,496.5)
Cargo Width	66.4 (1,686.9)	66.4 (1,686.9)	66.4 (1,686.9)
Distance Between Wheelhouses	51 (1,295.4)	51 (1,295.4)	51 (1,295.4)
Depth	20.0 (508.6)	20.1 (511.1)	20.2 (513.0)
Tailgate Opening Width in. – (mm)	60.4 (1,535.3)	60.4 (1,535.3)	60.4 (1,535.3)

Regular Cab Pickup

Model – Tire Size	2WD –265/70R17		4WD –265/70R17	
	6-ft. 4-in.	8-ft.	6-ft. 4-in.	8-ft.
Box Length				
Wheelbase (nominal)	120.5 (3,061.2)	140.5 (3,569.2)	120.5 (3,062.5)	140.5 (3,570.2)
Track, Front	68.0 (1,728.2)	68.0 (1,728.2)	68.2 (1,732.3)	68.2 (1,732.3)
Track, Rear	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)
Overall Length	209.0 (5,308.5)	231.0 (5,866.5)	209.0 (5,308.5)	231.0 (5,866.5)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	74.6 (1,894.2)	74.4 (1,889.2)	75.2 (1,910.4)	75.0 (1,906.2)

Ground Clearance

Front Axle	9.0 (229.3)	9.0 (229.2)	9.2 (232.6)	9.2 (232.7)
Rear Axle	8.7 (221.2)	8.7 (221.5)	8.6 (219.2)	8.6 (219.5)
Open Tailgate to Ground	34.8 (883.4)	34.6 (878.3)	35.0 (889.6)	34.9 (885.3)
Pickup Body Height	20.1 (511.1)	20.2 (513.0)	20.1 (511.1)	20.2 (513.0)
Approach Angle (degrees)	15.6	15.7	17.7	17.8
Departure Angle (degrees)	25.2	24.1	25.6	24.4
Ramp Breakover Angle (degrees)	21.5	19.2	22.9	20.5
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	32-gal. (121-liter) (standard)	26-gal. (98-liter) (standard)	32-gal. (121-liter) (standard)

**RAM**

2016 RAM 1500 SPECIFICATIONS

Quad Cab 6-ft. 4-in. Box Pickup

Model – Tire Size	2WD –265/70R17		4WD –265/70R17	
Wheelbase (nominal)	140.5 (3,569.2)		140.5 (3,570.2)	
Track, Front	68.0 (1,728.2)		68.2 (1,732.3)	
Track, Rear	67.5 (1,714.7)		67.5 (1,714.7)	
Overall Length	229.0 (5,816.5)		229.0 (5,816.5)	
Overall Width	79.4 (2,017.4)		79.4 (2,017.4)	
Overall Height	77.2 (1,960.2)		77.7 (1,974.8)	
Ground Clearance				
Front Axle	9.0 (229.2)		9.2 (232.7)	
Rear Axle	8.7 (221.5)		8.6 (219.5)	
Open tailgate to ground	34.6 (878.3)		34.9 (885.3)	
Pickup Body Height	20.1 (511.1)		20.1 (511.1)	
Approach Angle (degrees)	15.7		17.8	
Departure Angle (degrees)	25.1		25.4	
Ramp Breakover Angle (degrees)	19.2		20.5	
Fuel-Tank Capacity	26-gal. (98-liter) (standard)		26-gal. (98-liter) (standard)	
	32-gal. (121-liter) (optional)		32-gal. (121-liter) (optional)	

Model – Tire Size	2WD –265/70R17		4WD –265/70R17	
Box Length	<i>6-ft. 4-in.</i>	<i>8-ft.</i>	<i>6-ft. 4-in.</i>	<i>8-ft.</i>
Ground Clearance				
Front Axle	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)
Rear Axle	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)
Open Tailgate to Ground	33.4 (847.2)	34.9 (885.7)	35.6 (904.1)	36.9 (936.7)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.2	23.6
Ramp Breakover Angle without Skid Plate	17.1	20.6	22.5	24.2
Ramp Breakover Angle with Skid Plate	13.8	17.0	18.7	20.3
Ground Clearance without Skid Plate	7.4(187.2)	9.4 (239.8)	10.6 (269.5)	11.4 (290.8)
Ground Clearance with Skid Plate	6.7(169.3)	8.8 (222.8)	9.9 (252.8)	10.8 (273.7)

**RAM**

2016 RAM 1500 SPECIFICATIONS

Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

Crew Cab Pickup

Model – Tire Size	2WD –265/70R17		4WD –265/70R17	
	<i>5-ft. 7-in.</i>	<i>6-ft. 4-in.</i>	<i>5-ft. 7-in.</i>	<i>6-ft. 4-in.</i>
Box Length				
Wheelbase (nominal)	140.5 (3,569.2)	149.4 (3,795.3)	140.5 (3,570.2)	149.4 (3,795.2)
Track, Front	68.0 (1,728.2)	68.0 (1,728.2)	68.2 (1,732.3)	68.2 (1,732.3)
Track, Rear	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)
Overall Length	229.0 (5,816.5)	237.9 (6,042.6)	229.0 (5,816.5)	237.9 (6,042.6)
Overall Width	79.4 (2,017.4)	79.4 (2,016.6)	79.4 (2,017.4)	79.4 (2,016.6)
Overall Height	76.9 (1,953.8)	76.8 (1,950.6)	77.5 (1,967.9)	77.4 (1,965.1)
Ground Clearance				
Front Axle	9.0 (229.2)	9.1 (231.1)	9.2 (232.7)	9.2 (235.2)
Rear Axle	8.7 (221.5)	8.7 (220.5)	8.6 (219.5)	8.6 (218.3)
Open Tailgate to Ground	34.6 (878.3)	34.4 (874.0)	34.9 (885.3)	34.7 (880.8)
Pickup Body Height	20.0 (508.6)	20.1 (511.1)	20.0 (508.6)	20.1 (511.1)
Approach Angle (degrees)	15.7	16.0	17.8	18.0
Departure Angle (degrees)	25.1	24.9	24.7	25.2
Ramp Breakover Angle (degrees)	19.2	18.5	20.5	19.7
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

Crew Cab Pickup – Outdoorsman

Model – Tire Size	2WD –275/60R20		4WD –275/60R20	
	<i>5-ft. 7-in.</i>	<i>6-ft. 4-in.</i>	<i>5-ft. 7-in.</i>	<i>6-ft. 4-in.</i>
Box Length				
Wheelbase (nominal)	140.5 (3,569.4)	149.4 (3,795.8)	140.7 (3,573.5)	149.6 (3,799.6)
Track, Front	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,743.2)	68.6 (1,743.2)
Track, Rear	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)
Overall Length	229.0 (5,816.5)	237.9 (6,042.6)	229.0 (5,816.5)	237.9 (6,042.6)
Overall Width	79.4 (2,017.4)	79.4 (2,016.6)	79.4 (2,017.4)	79.4 (2,016.6)
Overall Height	77.6 (1,972.3)	77.5 (1,968.1)	78.5 (1,994.1)	78.4 (1,991.7)



2016 RAM 1500 SPECIFICATIONS

Ground Clearance				
Front Axle	9.6 (244.8)	9.6 (243.6)	9.8 (248.6)	9.8 (248.0)
Rear Axle	9.3 (237.0)	9.3 (235.0)	9.2 (233.2)	9.2 (233.1)
Open Tailgate to Ground	34.9 (887.7)	34.8 (883.9)	35.6 (903.5)	35.5 (902.3)
Pickup Body Height	20.0 (508.6)	20.1 (511.1)	20.0 (508.6)	20.1 (511.1)
Approach Angle (degrees)	21.3	21.0	23.9	22.9
Departure Angle (degrees)	21.4	21.2	22.1	22.1
Ramp Breakover Angle (degrees)	20.9	19.9	18.8	17.6
Ground Clearance without Skid Plate	10.3 (261.5)	10.3 (261.0)	NA	NA
Ground Clearance with Skid Plate	NA	NA	9.9 (252.2)	9.9 (251.6)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)
Track, Front	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)
Track, Rear	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	74.9 (1,902.1)	77.0 (1,955.1)	77.9 (1,979.2)	79.0 (2,006.1)
Ground Clearance				
Front Axle	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)
Rear Axle	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)
Open Tailgate to Ground	32.8 (832.8)	34.3 (871.2)	35.0 (889.6)	36.3 (922.2)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	23.0	24.8	25.6	27.1

**RAM****2016 RAM 1500
SPECIFICATIONS**

Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0
Ground Clearance without Skid Plate	6.7 (171.0)	8.8 (223.5)	10.0 (254)	10.8 (274.3)
Ground Clearance with Skid Plate	6.0 (153.1)	8.1 (205.7)	9.3 (236.2)	10.1 (256.5)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)
Track, Front	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)
Track, Rear	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	75.5 (1,917.4)	77.6 (1,970.4)	78.5 (1,994.5)	79.6 (2,021.4)
Ground Clearance				
Front Axle	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)
Rear Axle	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)
Open Tailgate to Ground	33.4 (847.2)	34.9 (885.7)	35.6 (904.1)	36.9 (936.7)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	15.2	19.8	22.4	23.9
Departure Angle (degrees)	23.7	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2
Ground Clearance without Skid Plate	7.4(187.2)	9.4 (239.8)	10.6 (269.5)	11.4 (290.8)
Ground Clearance with Skid Plate	6.7(169.3)	8.8 (222.8)	9.9 (252.8)	10.8 (273.7)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

**RAM**

2016 RAM 1500 SPECIFICATIONS

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>		<i>265/70R17</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2	
Wheelbase (nominal)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	
Track, Front	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)	
Track, Rear	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)	
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	
Overall Height	74.9 (1,902.1)	77.0 (1,955.1)	77.9 (1,979.2)	79.0 (2,006.1)	
Ground Clearance					
Front Axle	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)	
Rear Axle	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)	
Open Tailgate to Ground	32.8 (832.8)	34.3 (871.2)	35.0 (889.6)	36.3 (922.2)	
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	
Approach Angle (degrees)	15.2	19.7	21.8	22.9	
Departure Angle (degrees)	18.7	20.6	21.4	22.9	
Ramp Breakover Angle without Skid Plate	15.9	19.4	21.4	23.0	
Ramp Breakover Angle with Skid Plate	12.7	15.9	17.6	19.2	
Ground Clearance without Skid Plate	6.7 (171.0)	8.8 (223.5)	10.0 (254)	10.8 (274.3)	
Ground Clearance with Skid Plate	6.0 (153.1)	8.1 (205.7)	9.3 (236.2)	10.1 (256.5)	
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	

**RAM****2016 RAM 1500
SPECIFICATIONS****Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman**

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)
Track, Front	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)
Track, Rear	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	75.5 (1,917.4)	77.6 (1,970.4)	78.5 (1,994.5)	79.6 (2,021.4)
Ground Clearance				
Front Axle	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)
Rear Axle	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)
Open Tailgate to Ground	33.4 (847.2)	34.9 (885.7)	35.6 (904.1)	36.9 (936.7)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.2	23.6
Ramp Breakover Angle without Skid Plate	17.1	20.6	22.5	24.2
Ramp Breakover Angle with Skid Plate	13.8	17.0	18.7	20.3
Ground Clearance without Skid Plate	7.4(187.2)	9.4 (239.8)	10.6 (269.5)	11.4 (290.8)
Ground Clearance with Skid Plate	6.7(169.3)	8.8 (222.8)	9.9 (252.8)	10.8 (273.7)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

**RAM****2016 RAM 1500
SPECIFICATIONS****Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4**

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	149.5 (3,798.0)	149.5 (3,798.0)	149.5 (3,798.0)	149.5 (3,798.0)
Track, Front	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)
Track, Rear	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)
Overall Length	237.9 (6,042.6)	237.9 (6,042.6)	237.9 (6,042.6)	237.9 (6,042.6)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	74.7 (1,897.7)	76.8 (1,950.7)	77.8 (1,975.2)	78.8 (2,001.7)
Ground Clearance				
Front Axle	9.1 (231.6)	9.1 (231.6)	9.1 (231.6)	9.1 (231.6)
Rear Axle	8.6 (217.7)	8.6 (217.7)	8.6 (217.7)	8.6 (217.7)
Open Tailgate to Ground	32.6 (827.9)	34.1 (866.6)	34.8 (885.2)	36.1 (917.6)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	22.8	24.6	25.5	26.9
Ramp Breakover Angle (degrees)	15.3	18.7	20.5	22.2
Ground Clearance without Skid Plate	6.7 (170.0)	8.8 (222.7)	9.9 (252.4)	10.8 (273.7)
Ground Clearance with Skid Plate	6.0 (152.3)	8.1 (205.4)	9.3 (235.4)	10.1 (256.4)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)



2016 RAM 1500 SPECIFICATIONS

Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>	<i>275/60R20</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	149.5 (3,798.0)	149.5 (3,798.0)	149.5 (3,798.0)	149.5 (3,798.0)
Track, Front	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)
Track, Rear	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)
Overall Length	237.9 (6,042.6)	237.9 (6,042.6)	237.9 (6,042.6)	237.9 (6,042.6)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	75.4 (1,914.5)	77.5 (1,967.5)	78.4 (1,991.9)	79.5 (2,018.5)
Ground Clearance				
Front Axle	9.8 (247.9)	9.8 (247.9)	9.8 (247.9)	9.8 (247.9)
Rear Axle	9.2 (234.7)	9.2 (234.7)	9.2 (234.7)	9.2 (234.7)
Open Tailgate to Ground	32.3 (819.5)	34.8 (883.9)	35.5 (902.5)	36.8 (934.9)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	15.5	19.7	22.3	23.9
Departure Angle (degrees)	22.5	25.5	26.4	27.8
Ramp Breakover Angle (degrees)	16.4	19.8	21.7	23.3
Ground Clearance without Skid Plate	7.3 (185.8)	9.4 (239.0)	10.6 (268.7)	11.4 (290.0)
Ground Clearance with Skid Plate	6.6 (168.8)	8.7 (221.7)	9.9 (251.7)	10.7 (272.7)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

**RAM****2016 RAM 1500
SPECIFICATIONS****Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman**

<i>Tire Size</i>	<i>265/70R17</i>			
Suspension Mode	<i>Entry / Exit</i>	<i>Normal Ride Height</i>	<i>Off Road 1</i>	<i>Off Road 2</i>
Wheelbase (nominal)	149.5 (3,798.0)	149.5 (3,798.0)	149.5 (3,798.0)	149.5 (3,798.0)
Track, Front	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)
Track, Rear	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)
Overall Length	237.9 (6,042.6)	237.9 (6,042.6)	237.9 (6,042.6)	237.9 (6,042.6)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	74.7 (1,897.7)	76.8 (1,950.7)	77.8 (1,975.2)	78.8 (2,001.7)
Ground Clearance				
Front Axle	9.1 (231.6)	9.1 (231.6)	9.1 (231.6)	9.1 (231.6)
Rear Axle	8.6 (217.7)	8.6 (217.7)	8.6 (217.7)	8.6 (217.7)
Open Tailgate to Ground	32.6 (827.9)	34.1 (866.6)	34.8 (885.2)	36.1 (917.6)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	15.3	19.7	21.8	22.9
Departure Angle (degrees)	18.6	20.4	21.3	22.7
Ramp Breakover Angle without Skid Plate	15.3	18.7	20.5	22.2
Ramp Breakover Angle with Skid Plate	12.0	15.0	16.6	18.2
Ground Clearance without Skid Plate	6.7 (170.0)	8.8 (222.7)	9.9 (252.4)	10.8 (273.7)
Ground Clearance with Skid Plate	6.0 (152.3)	8.1 (205.4)	9.3 (235.4)	10.1 (256.4)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)



2016 RAM 1500 SPECIFICATIONS

Crew Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>		<i>275/60R20</i>		
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	149.5 (3,798.0)	149.5 (3,798.0)	149.5 (3,798.0)	149.5 (3,798.0)
Track, Front	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)
Track, Rear	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)
Overall Length	237.9 (6,042.6)	237.9 (6,042.6)	237.9 (6,042.6)	237.9 (6,042.6)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	75.4 (1,914.5)	77.5 (1,967.5)	78.4 (1,991.9)	79.5 (2,018.5)
Ground Clearance				
Front Axle	9.8 (247.9)	9.8 (247.9)	9.8 (247.9)	9.8 (247.9)
Rear Axle	9.2 (234.7)	9.2 (234.7)	9.2 (234.7)	9.2 (234.7)
Open Tailgate to Ground	32.3 (819.5)	34.8 (883.9)	35.5 (902.5)	36.8 (934.9)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	16.6	20.9	22.9	24.0
Departure Angle (degrees)	19.4	21.3	22.1	23.6
Ramp Breakover Angle without Skid Plate	16.4	19.8	21.7	23.3
Ramp Breakover Angle with Skid Plate	13.0	16.0	17.7	19.2
Ground Clearance without Skid Plate	7.3 (185.8)	9.4 (239.0)	10.6 (268.7)	11.4 (290.0)
Ground Clearance with Skid Plate	6.6 (168.8)	8.7 (221.7)	9.9 (251.7)	10.7 (272.7)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

**RAM****2016 RAM 1500
SPECIFICATIONS****ACCOMMODATIONS**

<i>Model</i>	<i>Regular Cab</i>	<i>Quad Cab</i>	<i>Crew Cab</i>
Seating Capacity, F/R	3/0 or 2/0	3/3 or 2/3	3/3 or 2/3
Front			
Head Room	39.9 (1,013.5)	41.0 (1,041.4)	41.0 (1,041.4)
Legroom	41.0 (1,041.4)	41.0 (1,041.4)	41.0 (1,041.4)
Shoulder Room	66.0 (1,676.4)	66.0 (1,676.4)	66.0 (1,676.4)
Hip Room	62.9 (1,598.7)	63.2 (1,605.3)	63.2 (1,605.3)
Seat Travel	9.0 (230.0)	9.0 (230.0)	9.0 (230.0)
Recliner Range (degrees)	85 (38 RWD, 47 FWD)	56 (38 RWD 18 FWD)	56 (38 RWD, 18 FWD)
Rear			
Head Room	N/A	39.7 (1,008.4)	39.9 (1,013.5)
Legroom	N/A	34.7 (880.9)	40.3 (1,023.3)
Shoulder Room	N/A	65.7 (1,668.8)	65.7 (1,668.8)
Hip Room	N/A	62.9 (1,598.3)	63.2 (1,605.3)
Interior Volume			
Front – cu. ft. (cu m)	62.5 (1.8)	64.2 (1.8)	64.2 (1.8)
Rear – cu. ft. (cu m)	N/A	52.4 (1.5)	61.1 (1.7)

Quad Cab 6ft. 4in. Box Pickup – Outdoorsman

<i>Model – Tire Size</i>	<i>2WD – 275/60R20</i>	<i>4WD – 275/60R20</i>
Wheelbase (nominal)	140.5 (3,569.4)	140.7 (3,573.5)
Track, Front	68.6 (1,742.2)	68.6 (1,743.2)
Track, Rear	68.0 (1,727.4)	68.0 (1,727.4)
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	77.9 (1,979.4)	78.8 (2,001.6)
Ground Clearance		
Front Axle	9.6 (244.8)	9.8 (248.6)
Rear Axle	9.3 (237.0)	9.2 (233.2)
Open tailgate to ground	(887.7)	(903.5)
Pickup Body Height	20.1 (511.1)	20.1 (511.1)
Approach Angle (degrees)	21.3	23.9
Departure Angle, (degrees)	21.4	22.1
Ramp Breakover Angle (degrees)	20.9	18.8



2016 RAM 1500 SPECIFICATIONS

Ground Clearance without Skid Plate	10.3 (261.5)	NA
Ground Clearance with Skid Plate	NA	9.9 (252.2)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>		<i>265/70R17</i>		
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)
Track, Front	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)
Track, Rear	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	75.2 (1,909.0)	77.2 (1,962.0)	78.2 (1,986.6)	79.2 (2,013.0)
Ground Clearance				
Front Axle	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)
Rear Axle	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)
Open Tailgate to Ground	32.8 (832.8)	34.3 (871.2)	35.0 (889.6)	36.3 (922.2)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	13.8	18.3	20.9	22.5
Departure Angle (degrees)	23.0	24.8	25.6	27.1
Ramp Breakover Angle (degrees)	15.9	19.4	21.4	23.0
Ground Clearance without Skid Plate	6.7 (171.0)	8.8 (223.5)	10.0 (254)	10.8 (274.3)
Ground Clearance with Skid Plate	6.0 (153.1)	8.1 (205.7)	9.3 (236.2)	10.1 (256.5)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

**RAM**

2016 RAM 1500 SPECIFICATIONS

Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4

<i>Tire Size</i>		<i>275/60R20</i>			
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2	
Wheelbase (nominal)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	
Track, Front	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)	
Track, Rear	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)	
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	
Overall Height	75.8 (1,924.4)	77.8 (1,977.4)	78.8 (2,002.0)	79.9 (2,028.4)	
Ground Clearance					
Front Axle	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	9.8 (248.5)	
Rear Axle	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	9.3 (235.0)	
Open Tailgate to Ground	33.4 (847.2)	34.9 (885.7)	35.6 (904.1)	36.9 (936.7)	
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	
Approach Angle (degrees)	15.2	19.8	22.4	23.9	
Departure Angle (degrees)	23.7	25.5	26.4	27.8	
Ramp Breakover Angle (degrees)	17.1	20.6	22.5	24.2	
Ground Clearance without Skid Plate	7.4(187.2)	9.4 (239.8)	10.6 (269.5)	11.4 (290.8)	
Ground Clearance with Skid Plate	6.7(169.3)	8.8 (222.8)	9.9 (252.8)	10.8 (273.7)	
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	



2016 RAM 1500 SPECIFICATIONS

Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman

<i>Tire Size</i>		<i>265/70R17</i>		
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)
Track, Front	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)	68.0 (1,728.2)
Track, Rear	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)	67.5 (1,714.7)
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	75.2 (1,909.0)	77.2 (1,962.0)	78.2 (1,986.6)	79.2 (2,013.0)
Ground Clearance				
Front Axle	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)	9.1 (232.3)
Rear Axle	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)	8.7 (220.0)
Open Tailgate to Ground	32.8 (832.8)	34.3 (871.2)	35.0 (889.6)	36.3 (922.2)
Pickup Body Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)
Approach Angle (degrees)	15.2	19.7	21.8	22.9
Departure Angle (degrees)	18.7	20.6	21.4	22.9
Ramp Breakover Angle without Skid Plate	15.9	19.4	21.4	23.0
Ramp Breakover Angle, with Skid Plate	12.7	15.9	17.6	19.2
Ground Clearance without Skid Plate	6.7 (171.0)	8.8 (223.5)	10.0 (254)	10.8 (274.3)
Ground Clearance with Skid Plate	6.0 (153.1)	8.1 (205.7)	9.3 (236.2)	10.1 (256.5)
Fuel-Tank Capacity	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)	26-gal. (98-liter) (standard)
	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)	32-gal. (121-liter) (optional)

**RAM****2016 RAM 1500
SPECIFICATIONS****Quad Cab 6ft. 4in. Box Pickup - Air Suspension 4x2 and 4x4 Outdoorsman**

<i>Tire Size</i>		<i>275/60R20</i>		
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road 1	Off Road 2
Wheelbase (nominal)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)
Track, Front	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)	68.6 (1,742.2)
Track, Rear	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)
Overall Width	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)	79.4 (2,017.4)
Overall Height	75.8 (1,924.4)	77.8 (1,977.4)	78.8 (2,002.0)	79.9 (2,028.4)

Crew Cab 5ft. 7in. Box Pickup - Air Suspension 4x2 and 4x4 Rebel

<i>Tire Size</i>		<i>285/70R17</i>		
Suspension Mode	Entry / Exit	Normal Ride Height	Off Road	
Wheelbase (nominal)	140.5 (3,569.4)	140.5 (3,569.4)	140.5 (3,569.4)	
Track, Front	68.6 (1,743.2)	68.6 (1,743.2)	68.6 (1,743.2)	
Track, Rear	68.0 (1,727.4)	68.0 (1,727.4)	68.0 (1,727.4)	
Overall Length	229.0 (5,816.5)	229.0 (5,816.5)	229.0 (5,816.5)	
Overall Width	81.5 (2,070.8)	81.5 (2,070.8)	81.5 (2,070.8)	
Overall Height	75.3 (1,913.7)	78.1 (1,984.6)	79.1 (2,010.2)	
Ground Clearance				
Front Axle	9.3 (237.3)	9.3 (237.3)	9.3 (237.3)	
Rear Axle	8.8 (223.6)	8.8 (223.6)	8.8 (223.6)	
Lift In Height	32.9 (835.3)	35.4 (899.1)	36.4 (924.7)	
Pickup Box Height	20.0 (508.6)	20.0 (508.6)	20.0 (508.6)	
Approach Angle, degrees	18.7	23.8	25.3	
Departure Angle, degrees	18.9	21.9	23.0	
Ramp Breakover Angle without Skid Plate, degrees	17.7	23.6	25.4	
Ramp Breakover Angle with Skid Plate, degrees	13.0	18.0	19.6	
Ground Clearance without Skid Plate	6.9 (175.5)	10.0 (253.5)	11.0 (279.1)	
Ground Clearance with Skid Plate	6.2 (157.8)	9.3 (236.3)	10.3 (261.9)	
Fuel-Tank Capacity	26-gal. (98-liter) (Standard)	26-gal. (98-liter) (Standard)	26-gal. (98-liter) (Standard)	
	32-gal. (121-liter) (Optional)	32-gal. (121-liter) (Optional)	32-gal. (121-liter) (Optional)	



RAM

2016 RAM 1500 SPECIFICATIONS

Cargo Box

Nominal Box Size	5 ft. 7 in.
SAE volume, cu. ft. (cu. m.)	50.3 (1.4)
Length at Floor, Tailgate Closed	67.4 (1,712.4)
Cargo Width	66.4 (1,686.9)
Distance Between Wheelhouses	51 (1,295.4)
Depth	20.0 (508.6)
Tailgate Opening Width in.	60.4 (1,535.3)

ACCOMMODATIONS

<i>Model</i>	<i>Crew Cab</i>
Seating Capacity, F/R	2/3

Front

Head Room	41.0 (1,040.5)
Legroom	40.9 (1,039.6)
Shoulder Room	65.9 (1,674.9)
Hip Room	62.9 (1,598.1)
Seat Travel	9.0 (230.0)
Recliner Range, degrees	56° (38 RWD, 18 FWD)

Rear

Head Room	39.9 (1,013.5)
Legroom	40.2 (1,022.3)
Shoulder Room	65.7 (1,670)
Hip Room	62.7 (1,592.7)

Interior Volume

Front – cu. ft. (cu m)	64.0 (1.8)
Rear – cu. ft. (cu m)	61.0 (1.7)

