

Canada: 2024 Alfa Romeo Stelvio

SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.
All dimensions are in millimetres (inches) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.*

GENERAL INFORMATION

Vehicle Type	Mid-size SUV, AWD
Assembly Plant	Cassino Assembly Plant, Cassino, Italy
EnerGuide Vehicle Class	Mid-size SUV

BODY/CHASSIS

Layout	Longitudinal front engine, AWD
Construction	Unitized high-strength steel body Aluminum front and rear vehicle frames, front shock towers, brakes, suspension components, doors, fenders, roof and hood Composite rear cross member Carbon fibre driveshaft

ENGINE: ALL-ALUMINUM 2.0-LITRE TURBOCHARGED 4-CYLINDER 280HP

Availability	Standard on Stelvio Sprint, Stelvio Ti and Stelvio Veloce
Type and Description	Inline-four, direct injection, turbo
Displacement	1,993 cc (121.7 cu. in.)
Bore x Stroke	84.0 x 89.9 (3.31 x 3.54)
Valve System	MultiAir2, SOHC, four valves per cylinder with silent chain driven timing drive Hollow assembled exhaust camshaft with end pivot roller finger followers and hydraulic lash adjusters
Turbocharger	Direct mount twin-scroll turbocharger with electric wastegate actuation. Intake manifold with liquid cooled charge air cooler.
Fuel Injection	Gasoline direct injection with injector centrally located in the combustion chamber Max injection pressure 2,900 psi

ENGINE: ALL-ALUMINUM 2.0-LITRE TURBOCHARGED 4-CYLINDER 280HP (CONTINUED)

Construction	Cylinder head: permanent mould air quenched cast aluminum alloy with integrated exhaust manifold Crankcase: precision and cast aluminum alloy with casted steel liners Crankshaft: super-finished forged nitride steel with journals offset from cylinder bore centreline Piston: forged aluminum cooled with pressure actuated oil jets
Power (SAE net)	280 hp (209 kW) @ 5,200 rpm (140 hp/litre)
Torque (SAE net)	306 lb.-ft. (415 N•m) @ 2,000 - 4,800 rpm
Redline on the Instrument Cluster	5,500 rpm
Max. Engine Speed	6,200 rpm
Fuel Requirement	Premium unleaded, 91 Octane (R+M)/2
EnerGuide Fuel Economy L/100km (MPG – imp.gal.) (city/hwy/combined)	22/28/24 (AWD)
Engine Assembly Plant	Termoli, Italy

BASED ON 2023 ENERGUIDE FUEL CONSUMPTION RATINGS. GOVERNMENT OF CANADA TEST METHODS USED.
YOUR ACTUAL FUEL CONSUMPTION WILL VARY BASED ON DRIVING HABITS AND OTHER FACTORS. FOR
ENERGUIDE INFORMATION, PLEASE VISIT THE GOVERNMENT OF CANADA WEBSITE:

WWW.VEHICLES.NRCAN.GC.CA

ENGINE: ALL-ALUMINUM 2.9-LITRE TWIN-TURBOCHARGED V-6 505HP AWD

Availability	Stelvio Quadrifoglio
Type and Description	V-6, 90-degree, direct injection
Displacement	2,891 cm ³ (176.4 cu. in.)
Bore x Stroke	86.5 x 82.0 (3.40 x 3.23)
Valve System	Chain-driven DOHC with intake and exhaust continuous camshaft phasing Four valves per cylinder roller finger actuated with hydraulic lash adjusters Mechanical cylinder deactivation on right bank
Turbochargers	Integrated IHI single-scroll turbo manifold with water charge air cooler
Fuel Injection	Port fuel injection and side mounted gasoline direct injection Max injection pressure 3,600 psi
Construction	Cylinder head and cover: aluminum alloy with integrated cam carrier Crankcase: closed deck aluminum alloy with wet steel liner Bedplate: aluminum alloy with integrated blow-by control reed valves

Crankshaft: super-finished forged nitride steel with single con-rod pin
Piston: forged aluminum cooled with twin oil jets

Compression Ratio	9.3:1
Power (SAE net)	505 hp (377 kW) @ 6,500 rpm (175 hp/litre)
Torque (SAE net)	443 lb.-ft. (600 N•m) @ 2500-5500 rpm

ENGINE: ALL-ALUMINUM 2.9-LITRE TWIN-TURBOCHARGED V-6 505HP AWD (CONTINUED)

Redline on the Instrument Cluster	6,500 rpm
Max. Engine Speed	7,400 rpm
Fuel Requirement	Premium unleaded, 91 Octane (R+M)/2
EnerGuide Fuel Economy	
L/100km (MPG – imp.gal.) (city/hwy/combined)	13.9/10.3/12.3 (20/27/23)
Engine Assembly Plant	Termoli, Italy

TRANSMISSION: 8HP50 EIGHT-SPEED AUTOMATIC (2.0-LITRE)

Availability	Stelvio Sprint, Stelvio Ti and Stelvio Veloce
Gearbox Type	AT8
Gearbox family	8HP50
Gear Ratios	
1st	5.000
2nd	3.200
3rd	2.143
4th	1.720
5th	1.314
6th	1.000
7th	0.822
8th	0.640
Transmission Type	AWD
Final Drive Ratio	3.73

TRANSMISSION: 8HP75 EIGHT-SPEED AUTOMATIC (2.9-LITRE)

Availability	Stelvio Quadrifoglio
Gearbox type	AT8
Gearbox family	8HP75
Gear Ratios	
1st	5.000

2nd	3.200
3rd	2.143
4th	1.720
5th	1.314
6th	1.000
7th	0.822
8th	0.640

TRANSMISSION: 8HP75 EIGHT-SPEED AUTOMATIC (2.9-LITRE) (CONTINUED)

Transmission Type	AWD
Final Drive Ratio	3.73

SUSPENSION

Front	Double wishbone with semi-virtual steering axle
Rear	AlfaLink™ design with vertical rod link (patented design)
Active Damping	Standard on Stelvio Quadrifoglio Included with Performance Packages on Stelvio Veloce

STEERING

Type	Rack and pinion with Variable Electric Assist
Ratio	12:1

BRAKES

Standard brake system	Standard on Stelvio Sprint, Stelvio Ti and Stelvio Veloce
Front	
Rotor size and type	330 x 28 (13.0 x 1.1)
Caliper size and type	Brembo four-piston calipers
Rear	
Rotor size and type	320 x 22 (12.5 x .86)
Caliper size and type	Single-piston calipers
High-performance Brembo brake system	Standard on Stelvio Quadrifoglio
Front	
Rotor size and type	360 x 32 (14.2 x 1.26) vented
Caliper size and type	Six-piston aluminum-monoblock calipers
Rear	
Rotor size and type	350 x 28 (13.8 x 1.1) vented

Caliper size and type	Four-piston aluminum-monoblock calipers
Ultra-high-performance Brembo Carbon Ceramic Material (CCM) brake system	Optional on Stelvio Quadrifoglio
Front	
Rotor size and type	390 x 36 (15.4 x 1.3) () two-piece, vented carbon ceramic matrix
Caliper size and type	Six-piston aluminum-monoblock calipers

BRAKES (CONTINUED)

Rear	
Rotor size and type	360 x 28 (14.2 x 1.1) two-piece, vented carbon ceramic matrix
Caliper size and type	Four-piston aluminum-monoblock calipers

DIMENSIONS AND CAPACITIES

Wheelbase	2,818 (110.9)
Track, Front	1,612 (63.5) — Stelvio Sprint, Stelvio Ti and Stelvio Veloce 1,555 (61.2) — Stelvio Quadrifoglio
Track, Rear	1,650 (65.0) — Stelvio Sprint, Stelvio Ti and Stelvio Veloce 1,608 (63.3) — Stelvio Quadrifoglio
Overall Length	4,688 (184.6) — Stelvio Sprint, Stelvio Ti and Stelvio Veloce 4,702 (185.1) — Stelvio Quadrifoglio
Overall Width (not including mirrors)	1,903 (74.9) — Stelvio Sprint, Stelvio Ti and Stelvio Veloce 1,955 (77.0) — Stelvio Quadrifoglio
Overall Height	1,677 (66.0) — Stelvio Sprint, Stelvio Ti and Stelvio Veloce 1,685 (66.3) — Stelvio Quadrifoglio
Behind Second-row Seats, litres (cu ft.)	525 (18.5)
Maximum Cargo Volume, litres (cu ft.)	1,600 (56.5)
Drag Coefficient (Cd)	0.32 — Stelvio Sprint, Stelvio Ti and Stelvio Veloce 0.34 — Stelvio Quadrifoglio
Towing Capacity, kg (lbs.)	1,361 (3,000) – Stelvio Sprint, Stelvio Ti and Stelvio Veloce
Fuel Tank Capacity, litre (gal.)	64 (16.9)
Ground Clearance	207 (8.1) — Stelvio AWD 201 (7.9) — Stelvio Quadrifoglio AWD
Curb Weight, kg (lbs.)	1,818 (4,007) — Stelvio AWD 1,956 (4,313) — Stelvio Quadrifoglio AWD

ACCOMMODATIONS

Seating Capacity, F/R	2/3
Headroom, F/R	1,020 (40.2) / 987 (38.9)
Legroom, F/R	929 (36.6) / 810 (31.9)
Shoulder Room, F/R	57.5/56.0
SAE Interior Volume, litres (cu ft.)	3,288 (116.1)

#