

LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

2008 Dodge Dakota EXTENDED CAB® FEATURE AVAILABILITY

	ST 4x2/ 4x4	SXT 4x2/ 4x4	SLT 4x2/ 4x4	TRX/T RX4 4x2/ 4x4	Sport 4x2/ 4x4	Laramie 4x2/ 4x4
EXTERIOR						
Bedliner, Under Rail	—	P	O	O	O	S
Bumpers and Fascias						
Black painted rear bumper	S	S	—	—	—	—
Mold-in-color front fascia	S	S	—	—	—	—
Body-color front fascia and rear bumper	—	—	S	S	S	—
Body-color front fascia and chrome rear bumper	—	—	—	—	—	S
Cargo Lamps, rear exterior	S	S	S	S	S	S
Colors						
Sunburst Orange, Detonator Yellow, Silver Metallic, Bright White, Brilliant Black, Electric Blue, Flame Red, Inferno Red	O	O	O	O	O	O
Decals/Badging						
Dakota	S	S	S	S	S	S
SXT	—	S	—	—	—	—
TRX (4x2 models only)	—	—	—	S	—	—
TRX4 Off-Road (4x4 models only)	—	—	—	S	—	—
Sport	—	—	—	—	S	—
Laramie	—	—	—	—	—	S
Defroster—Rear window (not available with sliding rear window if selected)	—	P	S	S	S	S
Dual Position Tailgate	S	S	S	S	S	S
Full Swing Rear Door	—	P	S	S	S	S
Fog Lamps	—	—	S	S	S	S
Glass						
Sunscreen, quarter windows	S	S	S	S	S	S
Tinted, windshield and front door windows	S	S	S	S	S	S
Grille						
Chrome	S	S	S	—	—	—
Accent	—	—	—	S	—	—
Sport-specific body-color	—	—	—	—	S	—
Chrome w/matching billets	—	—	—	—	—	S

Headlamps, halogen						
Manual	S	S	S	S	S	—
Black Bezels	—	—	—	S	—	—
Automatic	—	—	—	—	—	S
Mirrors (Black)						
Dual 5" x 7", Manual	S	S	S	S	S	S
Dual 6" x 9", Folding Power Heated (optional w/Trailer Tow Package; Utility Group on SXT)	—	P	O	O	O	O
Molding						
Bodyside, molded-in-color	—	—	—	S	S	—
Bodyside, chrome	—	—	—	—	—	S
Slush Mats (standard on TRX4 4x4)	—	—	—	S	—	—
Sliding rear window or defrost (sliding rear window n/a with defroster if selected)	—	P	S	S	S	S
Tailgate, dual position	S	S	S	S	S	S
Sidesteps, chrome/tubular	—	—	O	O	O	O
Spoiler, rear						
Molded-in color	S	S	S	S	S	S
Skid Plate Group (4x4 only, includes engine/transmission/transfer case and fuel tank skid plates and two front tow hooks – standard on TRX4 4x4 models)						
Tow Hooks (standard on TRX 4x2 models)	—	—	—	S	—	—
Trailer Tow Connection, four-pin	S	S	S	S	S	S
Trailer Tow Package -- Class IV hitch receiver; wiring harness with seven-circuit and four-circuit connectors; Heavy-duty Service Group consisting of heavy-duty engine cooling, auxiliary transmission cooler with automatic transmission, power steering cooler and 750 CCA battery. Includes dual 6" x 9" folding power heated mirrors (NA on ST)						
	—	P	O	O	O	O
Utility Rails	—	P	S	S	S	S
Wheel Fender Flares (molded-in-color)	—	—	—	S	—	—
Windshield Wipers, Variable-delay Intermittent	S	S	S	S	S	S
INTERIOR						
Assist Handles, Driver and Passenger	S	S	S	S	S	S
Climate Control—Air conditioning	S	S	S	S	S	S
Colors						
Khaki	O	O	O	O	O	O
Dark Slate	O	O	O	O	O	O
Red interior Accents	—	—	—	—	O	—
Console						
Floor	—	S	S	S	S	S
Overhead w/ compass, temperature, trip odometer	—	S	S	S	S	S
Courtesy/Map Lamp(s)						
Dual front	S	S	S	S	S	S
Rear dome/courtesy	S	S	S	S	S	S

Cruise Control	—	S	S	S	S	S
Floor Covering						
Carpet	S	S	S	S	S	S
Floor mats—Front, carpeted (color-keyed)	—	S	S	S	S	S
Instrument Cluster						
Analog Gauges—Speedometer, tachometer, coolant temperature, fuel	S	S	S	S	S	S
Power Accessory Delay	S	S	S	S	S	S
Power Outlet, Front	S	S	S	S	S	S
Power Windows/Locks/Mirrors/Keyless Entry	—	S	S	S	S	S
Seats						
Cloth Bucket Seats	S	S	—	—	—	—
Power Seats	—	—	S	—	—	—
YES Essentials® seat fabric	—	O	S	—	—	—
Heated Seats	—	O	O	O	O	O
TRX-specific Cloth Bucket Seats	—	—	—	S	—	—
Two-tone Embroidered Bucket Seats (cloth) w/increased side bolsters	—	—	—	—	S	—
Leather Bucket Seats	—	—	—	—	—	S
Bench Seats	—	—	O	—	—	—
Leather Bench Seats	—	—	—	—	—	O
Rear dual folding seats	O	S	S	S	S	S
Sound Systems						
AM/FM/CD/MP3 Radio	S	S	S	S	S	—
Six-disc AM/FM/MP3 Radio	—	—	P	P	P	S
Six-disc AM/FM/MP3/Navigation Radio	—	—	O	O	O	O
Alpine® six-speaker system with 276-watt amplifier (must have six-disc CD changer)	—	—	P	P	P	S
Satellite digital audio radio	—	P	S	S	S	S
SoundBox™ 508-watt audio system	—	—	O	O	O	O
Steering Column, Tilt	—	S	S	S	S	S
Steering Wheel, Leather-wrapped	—	—	—	—	S	S
Remote audio controls	—	—	P	P	P	S
Sun Visors, sliding	S	S	S	S	S	S

POWERTRAIN AND CHASSIS

Axle Ratio (rear):						
3.21 (std. 4x2 models)	S	S	S	—	—	—
3.55 (std. on 4x4 models and TRX 4x2)	S	S	S	S	—	—
3.92 (std. on TRX4 4x4)	—	P	O	S	—	—
3.55 w/3.7L engine (std. Sport models)	—	—	—	—	S	—
3.92 w/4.7L engine (std. Sport models, Laramie 4x4; opt. on Laramie 4x2)	—	—	—	—	O	S/O
3.55 w/4.7L engine (std. Laramie 4x2)	—	—	—	—	—	S
Brakes, Power						
Disc/Drum w/rear ABS	S	S	S	S	S	S

Four-wheel ABS	P	P	P	P	P	P
Differential, Anti-Spin	—	—	S	S	S	S
Engines/Transmissions						
3.7-liter V-6 w/ 6-spd. manual	S	S	S	S	—	—
3.7-liter V-6 w/4-spd. auto	O	O	O	O	S	—
4.7-liter V-8 w/5-spd. auto	—	—	O	O	O	S
Fuel Tank, 22-gallons	S	S	S	S	S	S
Heavy-duty Service Group (standard on TRX4 4x4) – Includes heavy-duty engine cooling, auxiliary transmission cooler with automatic transmission, power steering cooler and 750 CCA battery	—	—	—	S	—	—
Steering, Power Rack and Pinion	S	S	S	S	S	S
Tires						
P245/70R16 on/off-road black sidewall	S	S	S	—	—	—
P265/70R16 OWL (outline white letter) Rugged Trail	—	—	—	S	—	—
P265/65R18 on/off-road black sidewall	—	—	—	—	S	O
P265/65R16 tires	—	—	—	—	—	S
P265/65R18 OWL tires	—	—	O	—	—	O
Spare, Conventional	S	S	S	S	S	S
Transfer Cases						
NV233HD electric-shift part-time (four-wheel drive only)	S	S	S	S	S	S
NV244HD electric-shift full-time (four-wheel drive only); must have 4.7-liter engine and automatic transmission	—	—	—	O	O	O
Wheels						
Styled steel, 16" x 7"	S	—	—	—	—	—
Cast-aluminum, 16" x 8"	—	S	S	—	—	S
Chrome-clad aluminum, 18" x 8"	—	—	O	—	—	O
Silver painted aluminum, 18" x 8"	—	—	—	—	S	—
Black painted aluminum, 18" x 8"	—	—	—	—	O	—
Unique, TRX-specific cast-aluminum 16" x 8"	—	—	—	S	—	—

SAFETY & SECURITY

Air Bags

Advanced multi-stage front (driver and outboard passenger) with low-risk deployment system controlling level of passenger air bag deployment(a)	S	S	S	S	S	S
Passenger air bag cut-off switch—Ignition key operated(b)	S	S	S	S	S	S
Supplemental side-curtain air bags	P	P	P	P	P	P
Brake-Shift Interlock (with automatic transmission only)	S	S	S	S	S	S
Remote Start	—	—	P	P	P	S
Security Alarm	—	—	S	S	S	S
Sentry Key [®] Engine Immobilizer	—	—	S	S	S	S
LATCH (Lower Anchors and Tethers for CHildren)	S	S	S	S	S	S
Tire Pressure Monitoring System	S	S	S	S	S	S
UConnect [®] Hands-free Communications System	—	O	O	O	O	O

(a) Certified to federal regulations that allow less forceful air bags.
Always use seat belts.

Remember, a back seat is the safest place for children.

(b) Important, always remove key. A rearward-facing child seat may be used in the front-passenger seat only with the air bag turned off.

EQUIPMENT PACKAGES

Safety Group – Includes four-wheel ABS brakes and side curtain air bags.	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Utility Group – Includes trailer tow, 3.92 rear axle, utility rails, and bedliner	<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Convenience Group – Includes sliding rear window or defroster, full swing rear doors, and satellite digital radio	<input type="checkbox"/>	<input type="radio"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Sound Group – Includes 276-watt premium audio system, remote audio controls mounted on steering wheel, remote start and six-disc radio	<input type="checkbox"/>	<input type="checkbox"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="checkbox"/>

2008 Dodge Dakota CREW CAB® FEATURE AVAILABILITY

	ST 4x2/ 4x4	SXT 4x2/ 4x4	SLT 4x2/ 4x4	TRX/ TRX4 4x2/ 4x4	Sport 4x2/ 4x4	Laramie 4x2/ 4x4
EXTERIOR						
Bedliner, Under Rail	—	P	O	O	O	S
Bumpers and Fascias						
Black painted rear bumper	S	S	—	—	—	—
Mold-in-color front fascia	S	S	—	—	—	—
Body-color front fascia and rear bumper	—	—	S	S	S	—
Body-color front fascia and chrome rear bumper	—	—	—	—	—	S
Cargo Lamps, rear exterior	S	S	S	S	S	S
Colors						
Sunburst Orange, Detonator Yellow, Silver Metallic, Bright White, Brilliant Black, Electric Blue, Flame Red, Inferno Red	O	O	O	O	O	O
Decals/Badging						
Dakota	S	S	S	S	S	S
SXT	—	S	—	—	—	—
TRX (4x2 models only)	—	—	—	S	—	—
TRX4 Off-Road (4x4 models only)	—	—	—	S	—	—
Sport	—	—	—	—	S	—
Laramie	—	—	—	—	—	S
Defroster—Rear window (not available with sliding rear window if selected)	—	P	S	S	S	S
Dual Position Tailgate	S	S	S	S	S	S
Fog Lamps	—	—	S	S	S	S
Glass						
Sunscreen, quarter windows	S	S	S	S	S	S
Tinted, windshield and front door windows	S	S	S	S	S	S
Grille						
Chrome	S	S	S	—	—	—
Accent	—	—	—	S	—	—
Sport-specific body-color	—	—	—	—	S	—
Chrome w/matching billets	—	—	—	—	—	S
Headlamps, halogen						
Manual	S	S	S	S	S	—
Black Bezels	—	—	—	S	—	—
Automatic	—	—	—	—	—	S
Mirrors (Black)						
Dual 5" x 7", Manual	S	S	S	S	S	S
Dual 6" x 9", Folding Power Heated (optional w/Trailer Tow Package; Utility Group on SXT)	—	P	O	O	O	O

	ST 4x2/ 4x4	SXT 4x2/ 4x4	SLT 4x2/ 4x4	TRX/ TRX4 4x2/ 4x4	Sport 4x2/ 4x4	Laramie 4x2/ 4x4
Molding						
Bodyside, molded-in-color	—	—	—	S	S	—
Bodyside, chrome	—	—	—	—	—	S
Slush Mats (standard on TRX4 4x4)	—	—	—	S	—	—
Sliding rear window or defrost (sliding rear window n/a with defroster if selected)	—	P	S	S	S	S
Tailgate, dual position	S	S	S	S	S	S
Sidesteps, chrome/tubular	—	—	O	O	O	O
Spoiler, rear						
Molded-in color	S	S	S	S	S	S
Skid Plate Group (4x4 only, includes engine/transmission/transfer case and fuel tank skid plates and two front tow hooks – standard on TRX4 4x4 models)						
Sunroof, power	—	—	O	O	O	O
Tow Hooks (standard on TRX 4x2 models)	—	—	—	S	—	—
Trailer Tow Connection, four-pin	S	S	S	S	S	S
Trailer Tow Package -- Class IV hitch receiver; wiring harness with seven-circuit and four-circuit connectors; Heavy-duty Service Group consisting of heavy-duty engine cooling, auxiliary transmission cooler with automatic transmission, power steering cooler and 750 CCA battery. Includes dual 6" x 9" folding power heated mirrors (NA on ST)	—	P	O	O	O	O
Utility Rails	—	P	S	S	S	S
Wheel Fender Flares (molded-in-color)	—	—	—	S	—	—
Windshield Wipers, Variable-delay Intermittent	S	S	S	S	S	S
INTERIOR						
Assist Handles, Driver and Passenger	S	S	S	S	S	S
Climate Control—Air conditioning	S	S	S	S	S	S
Colors						
Khaki	O	O	O	O	O	O
Dark Slate	O	O	O	O	O	O
Red interior Accents	—	—	—	—	O	—
Console						
Floor	—	S	S	S	S	S
Overhead w/ compass, temperature, trip odometer	—	S	S	S	S	S
Courtesy/Map Lamp(s)						
Dual front	S	S	S	S	S	S
Rear dome/courtesy	S	S	S	S	S	S
Cruise Control	—	S	S	S	S	S
Floor Covering						
Carpet	S	S	S	S	S	S
Floor mats—Front, carpeted (color-keyed)	—	S	S	S	S	S

	ST 4x2/ 4x4	SXT 4x2/ 4x4	SLT 4x2/ 4x4	TRX/ TRX4 4x2/ 4x4	Sport 4x2/ 4x4	Laramie 4x2/ 4x4
Instrument Cluster						
Analog Gauges—Speedometer, tachometer, coolant temperature, fuel	S	S	S	S	S	S
Power Accessory Delay	S	S	S	S	S	S
Power Outlet, Front	S	S	S	S	S	S
Power Windows/Locks/Mirrors/Keyless Entry	—	S	S	S	S	S
Seats						
Cloth Bucket Seats	S	S	—	—	—	—
Power Seats	—	—	S	—	—	—
YES Essentials® seat fabric	—	O	S	—	—	—
Heated Seats	—	O	O	O	O	O
TRX-specific Cloth Bucket Seats	—	—	—	S	—	—
Two-tone Embroidered Bucket Seats (cloth) w/increased side bolsters	—	—	—	—	S	—
Leather Bucket Seats	—	—	—	—	—	S
Bench Seats	—	—	O	—	—	—
Leather Bench Seats	—	—	—	—	—	O
Rear Seat Storage -- Collapsible and removable under-seat cargo management system	—	—	S	S	S	S
Sound Systems						
AM/FM/CD/MP3 Radio	S	S	S	S	S	—
Six-disc AM/FM/MP3 Radio	—	—	P	P	P	S
Six-disc AM/FM/MP3/Navigation Radio	—	—	O	O	O	O
Alpine® six-speaker system with 276-watt amplifier (must have six-disc CD changer)	—	—	P	P	P	S
Satellite digital audio radio	—	P	S	S	S	S
Steering Column, Tilt	—	S	S	S	S	S
Steering Wheel, Leather-wrapped	—	—	—	—	S	S
Remote audio controls	—	—	P	P	P	S
Sun Visors, sliding	S	S	S	S	S	S

POWERTRAIN AND CHASSIS

Axle Ratio (rear):

3.21 (std. 4x2 models)	S	S	S	—	—	—
3.55 (std. on 4x4 models and TRX 4x2)	S	S	S	S	—	—
3.92 (std. on TRX4 4x4)	—	P	O	S	—	—
3.55 w/3.7L engine (std. Sport models)	—	—	—	—	S	—
3.92 w/4.7L engine (std. Sport models, Laramie 4x4; opt. on Laramie 4x2)	—	—	—	—	O	S/O
3.55 w/4.7L engine (std. Laramie 4x2)	—	—	—	—	—	S

Brakes, Power

Disc/Drum w/rear ABS	S	S	S	S	S	S
Four-wheel ABS	P	P	P	P	P	P

	ST 4x2/ 4x4	SXT 4x2/ 4x4	SLT 4x2/ 4x4	TRX/ TRX4 4x2/ 4x4	Sport 4x2/ 4x4	Laramie 4x2/ 4x4
Differential, Anti-Spin	—	—	S	S	S	S
Engines/Transmissions						
3.7-liter V-6 w/ 6-spd. manual	S	S	—	—	—	—
3.7-liter V-6 w/4-spd. auto	O	O	S	S	S	—
4.7-liter V-8 w/5-spd. auto	—	—	O	O	O	S
Fuel Tank, 22-gallons	S	S	S	S	S	S
Heavy-duty Service Group (standard on TRX4 4x4) – Includes heavy-duty engine cooling, auxiliary transmission cooler with automatic transmission, power steering cooler and 750 CCA battery	—	—	—	S	—	—
Steering, Power Rack and Pinion	S	S	S	S	S	S
Tires						
P245/70R16 on/off-road black sidewall	S	S	S	—	—	—
P265/70R16 OWL (outline white letter) Rugged Trail	—	—	—	S	—	—
P265/65R18 on/off-road black sidewall	—	—	—	—	S	O
P265/65R16 tires	—	—	—	—	—	S
P265/65R18 OWL tires	—	—	O	—	—	O
Spare, Conventional	S	S	S	S	S	S
Transfer Cases						
NV233HD electric-shift part-time (four-wheel drive only)	S	S	S	S	S	S
NV244HD electric-shift full-time (four-wheel drive only); must have 4.7-liter engine and automatic transmission	—	—	—	O	O	O
Wheels						
Styled steel, 16" x 7"	S	—	—	—	—	—
Cast-aluminum, 16" x 8"	—	S	S	—	—	S
Chrome-clad aluminum, 18" x 8"	—	—	O	—	—	O
Silver painted aluminum, 18" x 8"	—	—	—	—	S	—
Black painted aluminum, 18" x 8"	—	—	—	—	O	—
Unique, TRX-specific cast-aluminum 16" x 8"	—	—	—	S	—	—
SAFETY & SECURITY						
Air Bags						
Advanced multi-stage front (driver and outboard passenger) with low-risk deployment system controlling level of passenger air bag deployment(a)	S	S	S	S	S	S
Passenger air bag cut-off switch—Ignition key operated(b)	S	S	S	S	S	S
Supplemental side-curtain air bags	P	P	P	P	P	P
Brake-Shift Interlock (with automatic transmission only)	S	S	S	S	S	S
Remote Start	—	—	P	P	P	S
Security Alarm	—	—	S	S	S	S
Sentry Key [®] Engine Immobilizer	—	—	S	S	S	S
LATCH (Lower Anchors and Tethers for CHildren)	S	S	S	S	S	S
Tire Pressure Monitoring System	S	S	S	S	S	S

	ST 4x2/ 4x4	SXT 4x2/ 4x4	SLT 4x2/ 4x4	TRX/ TRX4 4x2/ 4x4	Sport 4x2/ 4x4	Laramie 4x2/ 4x4
--	-------------------	--------------------	--------------------	-----------------------------	----------------------	------------------------

UConnect® Hands-free Communications System

—	○	○	○	○	○	○
---	---	---	---	---	---	---

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts.

Remember, a back seat is the safest place for children.

(b) Important, always remove key. A rearward-facing child seat may be used in the front-passenger seat only with the air bag turned off.

EQUIPMENT PACKAGES

Safety Group – Includes four-wheel ABS brakes and side curtain air bags.

○	○	○	○	○	○	○
---	---	---	---	---	---	---

Utility Group – Includes trailer tow, 3.92 rear axle, utility rails, and bedliner

—	○	—	—	—	—	—
---	---	---	---	---	---	---

Convenience Group – Includes sliding rear window or defroster and satellite digital radio

—	○	—	—	—	—	—
---	---	---	---	---	---	---

Sound Group – Includes 276-watt premium audio system, remote audio controls mounted on steering wheel, remote start and six-disc radio

—	—	○	○	○	—	—
---	---	---	---	---	---	---

2008 Dodge Dakota

SPECIFICATIONS

Dimensions are in inches (millimeters) unless otherwise noted.

All dimensions measured on ST model at curb weight with standard tires unless otherwise noted.

GENERAL INFORMATION

Assembly Plant	Dodge City (Warren, Michigan)
Introduction Date	October 2004
EPA Vehicle Class	Extended Cab [®] and Crew Cab [®] pickup

ENGINE: NEXT-GENERATION 3.7-LITER, SOHC, 12-VALVE SMPI V-6 MAGNUM[®]

Availability	Std. —ST, SXT, SLT, TRX/TRX4, Sport
Type and Description	90° V-6, liquid-cooled with balance shaft
Displacement	226 cu. in. (3701 cu. cm)
Bore x Stroke	3.66 x 3.57 (93.0 x 90.8)
Valve System	Chain-driven SOHC, 12 valves, hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Cast-iron block and bedplate, aluminum alloy heads, balance shaft
Compression Ratio	9.7:1
Power (estimated SAE net)	210 bhp (157 kW) @ 5,200 rpm (58.1 bhp/L)
Torque (estimated SAE net)	235 lb.-ft. (319 N•m) @ 4,000 rpm
Max. Engine Speed	6,000 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R + M)/2
Oil Capacity	5.0 qt. (4.7L) SAE 5W/20
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors, and internal engine features (a)
Estimated EPA Fuel Economy mpg (City/Hwy)	2WD: 16/22—manual trans., 17/22—auto. trans. 4WD: 16/20—manual trans., 15/19—auto. trans.

NEXT-GENERATION 4.7-LITER (Corsair), SOHC, 16-VALVE SMPI V-8

Availability	Opt.—SLT, TRX/TRX4, Sport; std.—Laramie
Type and Description	V-type, liquid-cooled
Displacement	287 cu. in. (4701 cu. cm)
Bore x Stroke	3.66 x 3.40 (93.0 x 86.5)
Valve System	Chain-driven SOHC, 16 valves, hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	9.0:1—standard output
Power (SAE Net)	302 bhp (224 kW) @ 4,600 rpm (64.2 bhp/L)—standard output
Torque (SAE Net)	329 lb.-ft. (454 N•m) @ 3,600 rpm—standard output
Max. Engine Speed	5,750 rpm

Fuel Requirement	E85 (Ethanol) or Unleaded regular, 87 octane (R+M)/2—Normal
Oil Capacity	6 qt. (5.7L)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors, and internal engine features (a)
Estimated EPA Fuel Economy mpg (City/Hwy)	Standard Output: 16/22—2WD 15/21—4WD auto. trans.

(a) Meets federal Bin 10A emission standards and California LEV1 standards.

GETRAG 238—MANUAL SIX-SPEED OVERDRIVE

Availability	Std.—3.7
Description	Synchronized in all gears
Gear Ratios	
1st	4.23
2nd	2.53
3rd	1.67
4th	1.23
5th	1
6th	0.79
Reverse	3.84
Overall Top Gear	2.54 with 3.21 axle ratio, 2.80 with 3.55 axle ratio, 42RLE—Automatic, four-speed overdrive

42RLE—Automatic, four-speed overdrive

Availability	Available with 3.7L engine
Description	Clutch-selected planetary gear sets full electronic control, electronically-controlled torque converter clutch
Gear Ratios	
1st	2.84
2nd	1.57
3rd	1
4th	0.69
Overall Top Gear	2.45 with 3.55 axle ratio, 2.74 with 3.92 axle ratio 5-45RFE, automatic five-speed overdrive

5-45RFE—AUTOMATIC, FIVE-SPEED OVERDRIVE

Availability	Included with 4.7L engines
Description	Clutch-selected planetary gear sets, full electronic control, electronically-controlled torque converter clutch
Gear Ratios	
1st	3
2nd	1.67—upshift; 1.50—kick-down

3rd	1
4th	0.75
5th	0.67
Overall Top Gear	2.34 with 3.55 axle ratio or 2.59 with 3.92 axle ratio

NV233HD

Availability	Standard
Shift Mechanism	Electrical/electronic
Operating Modes	Neutral; 2WD; 4WD High, locked; 4WD Low, locked
Low Range Ratio	2.72
Center Differential	None

NV244HD

Availability	Optional on TRX/TRX4, Sport and Laramie
Shift Mechanism	Electrical/electronic
Operating Modes	Neutral; 4WD High, full-time; 4WD High, locked; 4WD Low, locked
Low Range Ratio	2.72
Center Differential Type	Planetary with lock
Torque Split, F/R	48/52

ELECTRICAL SYSTEM

Alternator	136-amp
Battery	Maintenance-free, top-terminal 600 CCA—std.; 750 CCA—opt.

BODY AND FRAME

Description	2WD	4WD
Layout	Longitudinal front engine, rear drive	Longitudinal front engine with transfer case for rear-wheel drive or four-wheel drive
Construction	Ladder-type frame, steel body mounted on rubber isolators	Ladder-type frame, steel body mounted on rubber isolators

SUSPENSION

Front	Upper and lower "A" arms, coil springs over gas-pressure shock absorbers, link-type stabilizer bar
Rear	Live axle, multi-leaf two-stage longitudinal springs, staggered gas-pressure shock absorbers

STEERING

Type	Power rack and pinion
Overall Ratio	17.4:1
Turning Diameter (Curb-to-curb)	44.0 ft. (13.4 m)
Steering Turns (Lock-to-lock)	3.18

BRAKES

Front	
Availability	Standard
Size and Type	12.3 x 1.1 (312 x 28) vented disc with 2.13 (54) dual-piston sliding caliper(a)
Swept Area	248 sq. in. (1604 sq. cm)
Rear	
Availability	Standard
Size and Type	11.6 x 2.28 (295 x 58) drum with ABS
Swept Area	166.6 sq. in. (1076 sq. cm)
Power Assist	
Availability	Standard
Type	9.06 (230) Tandem-diaphragm vacuum

FUEL SYSTEM

Fuel Tank Capacity	22 gal. (83L)
--------------------	---------------

(a) Available with ABS.

DIMENSIONS AND CAPACITIES(a)*2WD*

	Extended Cab	Crew Cab
Wheelbase	131.3 (3335.3)	131.3 (3335.3)
Track, Front	62.8 (1594.5)	62.8 (1594.5)
Track, Rear	62.9 (1598)	62.9 (1598)
Overall Length	218.5 (5549.9)	218.5 (5549.9)
Overall Width(a)	71.7 (1821.7) (TRX 76.4 [1940.6])	71.7 (1821.7) (TRX 76.4 [1940.6])
Overall Height	68.6 (1743.2)	68.7 (1744.7)
Tailgate Load Height	31.9 (809.6)	31.9 (809.6)
Ground Clearance		
Front Suspension (Lowest Point)	7.9 (201.9)	7.9 (201.9)
Rear Axle	8.1 (205.1)	8.1 (205.1)
Approach Angle	21.9°	21.9°
Ramp Breakover Angle	19.9°	19.9°
Departure Angle	22.6°	22.6°
Frontal Area, sq. ft. (sq. m) (estimated)	30.3 (2.81)	30.3 (2.81)
Drag Coefficient (estimated)	0.452	0.457
CdA, sq. ft.	13.7	13.7

4WD

	Extended Cab	Crew Cab
--	---------------------	-----------------

Wheelbase	131.3 (3335.3)	131.3 (3335.3)
Track, Front	62.8 (1594.5)	62.8 (1594.5)
Track, Rear	62.9 (1598)	62.9 (1598)
Overall Length	218.5 (5549.9)	218.5 (5549.9)
Overall Width	71.7 (1821.7) (TRX 76.4 [1940.6])	71.7 (1821.7) (TRX 76.4 [1940.6])
Overall Height	68.6 (1741.4)	68.6 (1742.9)
Tailgate Load Height	31.8 (808.9)	31.8 (808.9)
Ground Clearance		
Front Suspension (Lowest Point)	7.9 (201.9)	7.9 (201.9)
Rear Axle	8.0 (203.8)	8.0 (203.8)
Approach Angle	21.9°	21.9°
Ramp Breakover Angle	19.6°	19.6°
Departure Angle	22.5°	22.5°
Frontal Area, sq. ft. (sq. m) (estimated)	30.3 (2.81)	30.3 (2.81)
Drag Coefficient (estimated)	0.452	0.457
CdA, sq. ft.	13.7	13.7

(a) At seating reference point.

CARGO BOX DIMENSIONS

	Extended Cab	Crew Cab
Nominal Box Length, ft.	6.4	5.3
Length at Floor, Tailgate Closed	78.8 (2001.5)	64.9 (1648.1)
Length at Floor, Tailgate Open	100.3 (2546.6)	86.3 (2193.1)
Interior Width, Maximum	59.6 (1514.0)	59.6 (1514.0)
Distance Between Wheelhouses	45.2 (1146.9)	45.2 (1148.0)
Tailgate Opening Width	59.6 (1514.0)	59.6 (1514.0)
Depth	17.6 (446.9)	17.6 (446.9)
Volume, cu. ft. (cu. m)	46.6 (1.32)	38.2 (1.082)

ACCOMMODATIONS

	Extended Cab	Crew Cab
Seating Capacity, F/R	2 or 3/0 or 2	2 or 3/3
Front		
Head Room	39.6 (1005.3)	39.9 (1013.1)
Leg Room	41.9 (1063.1)	41.9 (1063.1)
Shoulder Room	57.7 (1466)	57.7 (1466)
Hip Room	54.9 (1394.0)	54.9 (1394.0)
Step Height	4x2: 20.4 (518.0) 4x4: 20.3 (515.8)	4x2: 20.4 (518.0) 4x4: 20.3 (515.8)
Interior Volume, cu. ft. (cu. m)	55.3 (1.57)	55.8 (1.58)
Seat Travel	8.7 (220)—driver 7.5 (190)—passenger	8.7 (220)—driver 8.7 (220)—passenger
Recliner Range	53°	53°
Rear		
Head Room	36.5 (928.3)	38.4 (974.2)
Leg Room—min.	32.1 (815.4)	36.4 (925.1)
Knee Clearance	-4.1 (-105.2)	3.0 (75.0)
Shoulder Room	57.4 (1458.3)	57.5 (1460.7)
Hip Room	56.9 (1446.2)	56.0 (1460.7)
Interior Volume, cu. ft. (cu. m)	39.0 (1.10)	46.5 (1.32)
Cab Cargo Volume		
(Rear Seat Up), cu. ft. (cu. m)	30.0 (0.85)	37.1 (1.05)

2008 DODGE DAKOTA CURB WEIGHT AND PAYLOAD
(BASE WEIGHTS CAN CHANGE)

<i>DAKOTA EXTENDED CAB 2WD SHORT BED ST</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1710	4296	2483	1813	3100	3600	7700	3250
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1720	4291	2469	1821	3100	3600	9000	4550
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1720	4291	2469	1821	3100	3600	9300	4850
1. Payload = GVWR - Curb Wt. 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs. Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)													

<i>DAKOTA CREW CAB 2WD SHORT BED ST</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1630	4381	2487	1894	3100	3600	7700	3150
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1630	4376	2474	1903	3100	3600	9000	4450
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1630	4476	2474	1903	3100	3600	9300	4750
1. Payload = GVWR - Curb Wt. 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs. Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)													

<i>DAKOTA EXTENDED CAB 2WD SHORT BED SXT</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1710	4296	2483	1813	3100	3600	7700	3250
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1720	4291	2469	1821	3100	3600	9000	4550
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1720	4291	2469	1821	3100	3600	9300	4850
1. Payload = GVWR - Curb Wt. 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs. Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)													

DAKOTA CREW CAB 2WD SHORT BED SXT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1630	4381	2487	1894	3100	3600	7700	3150
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1630	4376	2474	1903	3100	3600	9000	4450
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1630	4376	2474	1903	3100	3600	9300	4750

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB 2WD SHORT BED SLT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1680	4329	2484	1845	3100	3600	7700	3250
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1690	4324	2471	1854	3100	3600	9000	4550
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1690	4324	2471	1854	3100	3600	9300	4850
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1520	4494	2579	1915	3100	3600	10,500	5850
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1520	4494	2579	1915	3100	3600	11,700	7050

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB 2WD SHORT BED TRX

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1660	4354	2510	1844	3100	3600	7700	3200
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1660	4350	2497	1853	3100	3600	9000	4500
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1660	4350	2497	1853	3100	3600	9300	4800
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1490	4519	2604	1914	3100	3600	10,500	5850
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1490	4519	2604	1914	3100	3600	11,700	7050

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB 2WD SHORT BED SLT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1570	4437	2486	1951	3100	3600	9000	4400
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1570	4437	2486	1951	3100	3600	9300	4700
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1400	4614	2592	2022	3100	3600	10,500	5750
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1400	4614	2592	2022	3100	3600	11,700	6950

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB 2WD SHORT BED TRX

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1570	4437	2486	1951	3100	3600	9000	4400
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1570	4437	2486	1951	3100	3600	9300	4700
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1400	4614	2592	2022	3100	3600	10,500	5750
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1400	4614	2592	2022	3100	3600	11,700	6950

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB 2WD SHORT BED SPORT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1690	4325	2472	1854	3100	3600	9000	4550
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1690	4325	2472	1854	3100	3600	9300	4850
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1520	4494	2579	1915	3100	3600	10,500	5850
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1520	4494	2579	1915	3100	3600	11,700	7050

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB 2WD SHORT BED SPORT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.55	8.25	6010	1570	4437	2486	1951	3100	3600	9000	4400
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1570	4437	2486	1951	3100	3600	9300	4700
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1400	4614	2592	2022	3100	3600	10,500	5750
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1400	4614	2592	2022	3100	3600	11,700	6950

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB LARAMIE 2WD SHORT BED

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1460	4553	2604	1950	3100	3600	10,500	5800
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1460	4553	2604	1950	3100	3600	11,700	7000

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB LARAMIE 2WD SHORT BED

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1480	4529	2592	1937	3100	3600	10,500	5800
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1480	4529	2592	1937	3100	3600	11,700	7000

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB 4WD SHORT BED ST

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	8.25	6010	1530	4485	2659	1826	3600	3600	8500	3850
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1520	4485	2649	1837	3600	3600	9300	4650

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB 4WD SHORT BED ST

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	8.25	6010	1440	4573	2649	1924	3600	3600	8500	3800
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1440	4573	2639	1935	3600	3600	9300	4600

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB 4WD SHORT BED SXT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	8.25	6010	1530	4485	2659	1826	3600	3600	8500	3850
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1520	4485	2649	1837	3600	3600	9300	4650

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB 4WD SHORT BED SXT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	8.25	6010	1440	4573	2649	1924	3600	3600	8500	3800
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1440	4573	2639	1935	3600	3600	9300	4600
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	8.25	6010	1240	4766	2737	2029	3600	3600	10,500	5800
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	8.25	6010	1240	4766	2737	2029	3600	3600	11,700	6800

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB 4WD SHORT BED SLT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1470	4536	2661	1875	3600	3600	9300	4600
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1280	4730	2755	1975	3600	3600	10,500	5600
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1280	4730	2755	1975	3600	3600	11,700	6800

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB 4WD SHORT BED TRX

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	8.25	6010	1470	4535	2671	1865	3600	3600	8500	3800
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1470	4536	2661	1875	3600	3600	9300	4600
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1280	4730	2756	1975	3600	3600	10,500	5600
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1280	4730	2756	1975	3600	3600	11,700	6800

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB 4WD SHORT BED SLT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1430	4585	2634	1951	3600	3600	9300	4550
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1230	4782	2733	2049	3600	3600	10,500	5550
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1230	4782	2733	2049	3600	3600	11,700	6750

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB 4WD SHORT BED TRX

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1430	4585	2634	1951	3600	3600	9300	4550
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1230	4782	2733	2049	3600	3600	10,500	5550
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1230	4782	2733	2049	3600	3600	11,700	6750

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB 4WD SHORT BED SPORT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1470	4536	2661	1875	3600	3600	9300	4600
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1280	4730	2755	1975	3600	3600	10,500	5600
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1280	4730	2755	1975	3600	3600	11,700	6800

1. Payload = GVWR - Curb Wt.
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB 4WD SHORT BED SPORT

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO w/VLP (DGV)	3.92	8.25	6010	1430	4585	2634	1951	3600	3600	9300	4550
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1230	4782	2733	2049	3600	3600	10,500	5550
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1230	4782	2733	2049	3600	3600	11,700	6750

1. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA EXTENDED CAB 4WD SHORT BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1270	4744	2786	1958	3100	3600	11,700	6800

1. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

DAKOTA CREW CAB 4WD SHORT BED LARAMIE

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
4.7L V-8 (EVE)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1150	4859	2768	2091	3100	3600	11,700	6700

1. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)